



000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SENTRON™/MC CG 40 PLUS

Product code : STNCGPIBC, STNCGPDRM, STNCGPDCT, STNCGP,
STNCGPBLK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : SENTRON CG 40 PLUS is a low ash Natural Gas Engine Oil designed for use in 4-stroke stationary spark-ignition engines running in contaminated gas applications such as landfill, biogas or sewage gas.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details : Petro-Canada Europe Lubricants Limited
Wellington House, Starley Way
Birmingham International Park Solihull B37 7HB
United Kingdom

E-mail address of person responsible for the SDS : EUSDS@suncor.com

1.4 Emergency telephone number

Emergency telephone number : Suncor Energy: +1 403-296-3000;
Poison Control Centre: Consult local telephone directory for emergency number(s).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

Additional Labelling:

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
SENTRON™/MC CG 40 PLUS



000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

EUH208 May produce an allergic reaction.
EUH210 Safety data sheet available on request.
Contains: Calcium long chain alkaryl sulfonate and Salts of alkyl hydroxybenzoic acids

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification	Concentration
distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-0055	Asp. Tox. 1; H304	70 - 90 %
lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0 276-737-9 01-2119474878-16-0001	Asp. Tox. 1; H304	1 - 10 %
Polyolefin polyamine succinimide	84605-20-9 617-593-2	Aquatic Chronic 4; H413	1 - 2.5 %
Phenol, 2,2'-polythiobis[4-C8-30-alkyl derivs., calcium salts, overbased	90480-91-4 291-829-9	Aquatic Chronic 4; H413	1 - 2.5 %

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Wash clothing before reuse.
Seek medical advice.

In case of eye contact : Remove contact lenses.

000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.

If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : No information available.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Cool closed containers exposed to fire with water spray.

Hazardous combustion products : Carbon oxides (CO, CO₂), nitrogen oxides (NO_x), phosphorus oxides (PO_x), sulphur oxides (SO_x), zinc oxides (ZnO_x), calcium oxides (CaO_x), aldehydes and smoke and irritating vapours as products of incomplete combustion.

5.3 Advice for firefighters

Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.
Mark the contaminated area with signs and prevent access to unauthorized personnel.



000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Use only with adequate ventilation.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin, eyes and clothing.
Do not ingest.
Keep away from heat and sources of ignition.
Keep container closed when not in use.

Advice on protection against fire and explosion : None known.

Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.



000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye protection : Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : viscous liquid

Colour : amber

Odour : No odour or slight petroleum oil like.

Odour Threshold : No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
SENTRON™/MC CG 40 PLUS



000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

pH	:	No data available
Pour point	:	-27 °C (-17 °F)
Boiling point/boiling range	:	No data available
Flash point	:	283 °C (541 °F) Method: Cleveland open cup
Fire Point	:	289 °C (552 °F)
Auto-Ignition Temperature	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Low fire hazard. This material must be heated before ignition will occur.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	0.8742 kg/l (15 °C / 59 °F)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity		
Viscosity, kinematic	:	118.7 cSt (40 °C / 104 °F) 13.4 cSt (100 °C / 212 °F)
Explosive properties	:	Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

9.2 Other information

No data available

000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.
Stable under normal conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents, reducing agents and acids.

10.6 Hazardous decomposition products

Hazardous decomposition products : May release CO_x, SiO_x, H₂S, alkyl mercaptans, methacrylate monomers, aldehydes, smoke and irritating vapours when heated to decomposition.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:

lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist



000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

Skin corrosion/irritation

Product:

Remarks: No data available

Serious eye damage/eye irritation

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to bacteria :
Remarks: No data available

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Offer surplus and non-recyclable solutions to a licensed disposal company.
Waste must be classified and labelled prior to recycling or disposal.
Send to a licensed waste management company.
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14: Transport information

International Regulation

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

ADR: Not Regulated

ADN: Not Regulated

RID: Not Regulated

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The components of this product are reported in the following inventories:

DSL : On the inventory, or in compliance with the inventory

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

ELINCS : On the inventory, or in compliance with the inventory

15.2 Chemical Safety Assessment



000003001359

Version 4.0

Revision Date 2016/05/20

Print Date 2016/05/20

SECTION 16: Other information

Full text of H-Statements

- H304 : May be fatal if swallowed and enters airways.
- H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

- Aquatic Chronic : Chronic aquatic toxicity
- Asp. Tox. : Aspiration hazard

Further information

- For Copy of (M)SDS : Internet: lubricants.petro-canada.ca/msds
Europe, telephone: 00-800-7387-6000
For Product Safety Information: 1 905-804-4752

- Prepared by : Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.